

MAGNETIC RECORDING MEDIUM

Patent Number: JP63225918
Publication date: 1988-09-20
Inventor(s): FUJINO NAOHIKO; others: 04
Applicant(s):: MITSUBISHI ELECTRIC CORP
Requested Patent: ☐ JP63225918
Application Number: JP19870059531 19870313
Priority Number(s):
IPC Classification: G11B5/72
EC Classification:
Equivalents:

Abstract

PURPOSE: To prevent the reduction of reproduction output to a magnetic head by forming a protective layer of a fluorine-contg. silane coupling agent on a magnetic layer and interposing a silane coupling agent layer between the magnetic layer and the protective layer so as to nearly prevent the scattering and evaporation of a fluorine-contg. lubricant by the coupling agent layer.

CONSTITUTION: An Ni-P alloy underlayer 2 is formed on an Al alloy substrate 1 and a magnetic Ni-Co-P alloy layer 3 of a prescribed thickness is formed on the underlayer 2. A hard silicon oxide layer 4 of about 1,800Angstrom thickness is formed on the layer 3 by sputtering or other method and a silane coupling agent layer 5 is formed on the layer 4 by sputtering, dip coating or other method. Heat treatment is then carried out in the air at a prescribed temp. for a prescribed time to regulate the thickness of the layer 5 to about 30Angstrom. A protective layer 6 of a fluorine-contg. silane coupling agent is further formed on the layer 5 by spin coating.

BEST AVAILABLE COPY